


Celeron

HDMI

DVI

SIM Slot



Specifications

CPU	Intel® Celeron N3160
Frequency	1.60 GHz (Up to 2.24 GHz)
BIOS	AMI Source Code
Chipset	SOC
System Memory	1 x SO-DIMM, DDR3L-1600MHz Up to 8GB
GPU	Intel® HD Graphics
Graphic Engine	DirectX 11, OpenGL 4.0, OpenCL 1.2
Network Controller	Realtek RTL8111H Gigabit Ethernet
Audio	ALC662-VD
SIO	ITE8718
Rear I/O	2 x USB 3.0, 2 x USB 2.0 1 x HDMI (Max. 2560 x 1600 @60Hz) 1 x DVI (Max. 1920 x 1080 @60Hz) 1 x RJ45 1 x MIC-IN, 1 x AUDIO-OUT
Internal I/O	3 x USB 2.0 1 x Dual Channel 24-bit LVDS (Max. 1920 x 1080 @60Hz) 2 x RS232 4Bit x DI, 4Bit x DO 1 x Full-size Mini-PCIe for mSATA 1 x Full-size Mini-PCIe for WIFI/BT/3G/4G 1 x SIM Slot 1 x SPEAKER
Storage	2 x SATA, 1 x mSATA
JAHC	WatchDog Timer Auto Power On RTC
Operation System	Windows 7/8.1/10/Linux
Power Requirement	DC-IN/12V/19V
Dimensions (W x D)	170mm x 170mm (6.69" x 6.69")
Storage Temperature	-40°C ~ 75°C (-40 ~ 167 °F)
Operating Temperature	0 ~ 60°C (32 ~ 140 °F)
Relative Humidity	95% @ 60°C (non-condensing)

Features

- Intel® Celeron N3160 CPU
- 1 x SO-DIMM, DDR3L-1600MHz, Up to 8GB
- 1 x HDMI, 1 x DVI, 1 x LVDS
- 2 x SATA, 1 x mSATA
- 2 x USB3.0, 5 x USB2.0, 2 x RS232
- 1 x RJ45, 1 x Mini-PCIe for WIFI/BT/3G/4G, 1 x SIM Slot

Order Information

MI-N3160SL	CPU: Celeron N3160, RAM: Up to 8GB 1 x HDMI, 1 x DVI 2 x USB 3.0, 5 x USB 2.0, 2 x RS232, 1 x RJ45, 1 x SIM Slot, 1 x GPIO 2 x SATA, 1 x mSATA
------------	--

Dimensions and Drawing

