

Skylake


Dual Channel

DP

HDMI

VGA

SIM Slot



## Features

- Intel® H110+LGA1151 CPU
- 2 x U-DIMM, DDR4-2133MHz, Up to 32GB
- 2 x DP, 1 x HDMI, 1 x VGA
- 3 x SATA, 1 x mSATA
- 4 x USB3.0, 6 x USB2.0, 6 x RS232
- 2 x RJ45, 1 x Mini-PCIe for WIFI/BT/3G/4G, 1 x SIM Slot

## Specifications

CPU	Intel® H110 + LGA1151
BIOS	AMI Source Code
Chipset	H110
System Memory	2 x U-DIMM, DDR4-2133MHz Up to 32GB
GPU	Intel® HD Graphics 530
Graphic Engine	Direct X 11, OpenGL 4.3, OpenCL 1.2
Network Controller	2 x Realtek RTL8111H Gigabit Ethernet
Audio	ALC662-VD
SIO	ITE8782F
Rear I/O	4 x USB 3.0, 2 x USB 2.0 2 x DP ( Max. 4096 x 2304 @60Hz ) 1 x VGA ( Max. 2048 x 1536 @60Hz ) 1 x RS232 2 x RJ45 1 x MIC-IN, 1 x LINE-IN, 1 x LINE-OUT
Internal I/O	4 x USB 2.0 1 x HDMI ( Max. 4096 x 2304 @24Hz ) 5 x RS232 1 x PCIe x 16 1 x Full-size Mini-PCIe for mSATA 1 x Full-size Mini-PCIe for WIFI/BT/3G/4G 1 x SIM Slot
Storage	3 x SATA, 1 x mSATA
Operation System	Windows 7/8.1/10/Linux
Power Requirement	ATX 24 + 4pin
Dimensions ( W x D )	170mm x 170mm ( 6.69" x 6.69" )
Storage Temperature	-40°C ~ 75°C ( -40 ~ 167 °F )
Operating Temperature	0 ~ 60°C ( 32 ~ 140 °F )
Relative Humidity	95% @ 60°C ( non-condensing )

## Order Information

DT-H110DL-V	CPU: H110 + LGA1151, RAM: Up to 32GB 2 x DP, 1 x HDMI, 1 x VGA 4 x USB 3.0, 6 x USB 2.0, 6 x RS232, 2 x RJ45, 1 x PCIe x 16 3 x SATA, 1 x mSATA
-------------	---

## Dimensions and Drawing

