

Kabylake /Skylake

Desktop

HDMI

VGA

M.2

6xUSB



RoHS  

Features

- Intel® LGA1151 Socket 6th/7th Gen. Processor
- 2 x U-DIMM DDR4 Memory, Up to 32GB
- 1 x HDMI, 1 x VGA
- 1 x 2.5" SATA, 1 x mSATA, 1 x M.2 (2242/2280)
- 4 x USB3.0, 2 x USB2.0, 2 x RS232
- 1 x RJ45, 1 x Mini-PCIe for WiFi/BT

Specifications

CPU	Intel® LGA1151 Socket 6 th /7 th Gen.Processor
BIOS	AMI Source Code
Chipset	H110
System Memory	DDR4-2133MHz, 2 x U-DIMM, Up to 32GB
GPU	Intel® HD Graphics 520/620
Graphic Engine	Direct3D 2015, OpenGL 4.5, OpenCL 2.1
Display Interface	1 x VGA (Max. 2048 x 1536 @60Hz) 1 x HDMI (Max. 3840 x 2160 @30Hz)
Network Controller	Realtek RTL8111H Gigabit Ethernet
Ethernet	1 x RJ45
USB	4 x USB 3.0, 2 x USB 2.0
PS/2	1 x KB,1 x MS
Serial Port	2 x RS232
Rear Audio	1 x MIC-IN, 1 x LINE-OUT, 1 x LINE-IN
Front Audio	1 x MIC-IN, 1 x AUDIO-OUT
Mini-PCIe	1 x Full- size Mini-PCIe for mSATA 1 x Half-size Mini-PCIe for WiFi/BT
M.2	1 x M.2 (2242/2280) for SSD
Storage	1 x 2.5" SATA 1 x Full-size mSATA 1 x M.2 (2242/2280) for SSD
JAHC	WatchDog Timer Auto Power On RTC
Operation System	Windows 7/8.1/10 (64-bit)/Linux
Power Requirement	DC-IN/19V/4.74A
Dimensions (W x D x H)	236mm x 178.4mm x 50mm (9.29" x 7.02" x 1.97")
Fanless	No
Construction	Metal
Mounting (Optional)	VESA Mounting Kit (JZ 300)
Color	Black
Operating Temperature	0°C ~ 40°C (32 °F ~ 104 °F) at 0.7m/s Air Flow
Relative Humidity	95% @ 40°C (non-condensing)
Certification	CE, FCC Class B, CCC

Order Information

D360-E0000	Intel® LGA1151 Socket 6 th /7 th Gen.Processor
Packing List	2 x WiFi Antenna, 1 x Drive Disk, 1 x User Manual 1 x AC Power Cable, 1 x AC Power Adapter
Optional Item	VESA Mounting Kit (JZ 300)

Dimensions and Drawing

