

Kabylake

HDMI

2xDP

4K

SIM Slot

GPU



RoHS

Features

- Intel® Kabylake Processor
- 2 x SO-DIMM, DDR3L-1600MHz, Up to 32GB
- 2 x DP, 1 x HDMI
- 1 x 2.5" SATA, 1 x mSATA
- 2 x USB3.0, 2 x USB2.0, 1 x RS232
- 1 x RJ45, 1 x Mini-PCIe for WiFi/BT/3G/4G, 1 x SIM Slot

Specifications

CPU	Intel® Pentium 4415U/Core i3-7100U/Core i5-7200U
Frequency	2.30 GHz/2.40 GHz/2.50 GHz up to 3.10 GHz
BIOS	AMI Source Code
Chipset	SOC
System Memory	2 x SO-DIMM, DDR3L-1600MHz, Up to 32GB
GPU	NVIDIA GT730, SDDR3 2GB
Graphic Engine	DirectX12, OpenGL4.4 and OpenCL 1.2
Display Interface	1 x HDMI (Max. 4096 x 2304 @24Hz) 2 x DP (Max. 4096 x 2304 @24Hz)
Network Controller	Realtek RTL8111H Gigabit Ethernet
Ethernet	1 x RJ45
USB	2 x USB 3.0, 2 x USB2.0
Serial Port	1 x RS232
Audio	1 x MIC-IN, 1 x AUDIO-OUT & SPDIF
Mini-PCIe	1 x Full-size Mini-PCIe for mSATA 1 x Full-size Mini-PCIe for WIFI/BT/3G/4G
SIM	1 x SIM Slot
Storage	1 x 2.5" SATA 1 x Full-size mSATA
JAHC	WatchDog Timer Auto Power On RTC Remote Control
Operation System	Windows 10 (64-bit)/Linux
Power Requirement	DC-IN/19V/4.74A
Dimensions (W x D x H)	240mm x 173.4mm x 28mm (9.45" x 6.83" x 1.1")
Construction	Metal
Mounting (Optional)	Wall Mounting and VESA Mounting (JZ300)
Color	Black
Operating Temperature	0°C ~ 40°C (32°F ~ 140°F) at 0.7m/s Air Flow
Relative Humidity	95% @ 40°C (non-condensing)
Certification	CE, FCC Class B, CCC

Order Information

G367-G1-4415U30M0G	CPU: Pentium 4415U
G367-G1-7100U30M0G	CPU: Core i3-7100U
G367-G1-7200U30M0G	CPU: Core i5-7200U
Packing List	2 x WiFi Antenna, 1 x Drive Disk, 1 x User Manual, 1 x AC Power Cable, 1 x AC Power Adapter
Optional Item	VESA Mounting Kit (JZ 300)

Dimensions and Drawing

