


Skylake

Dual Channel

HDMI

DP



Features

- Intel® B150+LGA1151 CPU
- 2 x U-DIMM DDR4-2133MHz, Up to 32GB
- 2 x DP, 1 x HDMI
- 3 x SATA, 1 x mSATA
- 4 x USB3.0, 5 x USB2.0, 6 x RS232
- 2 x RJ45, 1 x Mini-PCIe for WIFI/BT/3G/4G, 1 x SIM Slot

Specifications

CPU	Intel® B150+LGA1151
BIOS	AMI Source Code
Chipset	B150
System Memory	2 x U-DIMM DDR4-2133MHz, Up to 32GB
Network Controller	2 x Realtek RTL8111H Gigabit Ethernet
Audio	ALC662-VD
SIO	ITE8782F
Rear I/O	4 x USB 3.0, 2 x USB 2.0 2 x DP (Max. 4096 x 2304 @60Hz) 1 x HDMI (Max. 4096 x 2304 @24Hz) 2 x RJ45 1 x RS232 1 x MIC-IN, 1 x LINE-IN, 1 x LINE-OUT
Internal I/O	3 x USB 2.0 5 x RS232 1 x PCIe16 1 x Full-size Mini-PCIe for mSATA 1 x Full-size Mini-PCIe for WIFI/BT/3G/4G 1 x SIM Slot
Storage	3 x SATA, 1 x mSATA
Operation System	Windows 7/8.1/10/Linux
Power Requirement	ATX 24+4pin
Dimensions (W x D)	170mm x 170mm (6.69" x 6.69")
Storage Temperature	-40°C ~ 75°C (-40 ~ 167°F)
Operating Temperature	0 ~ 60°C (32 ~ 140°F)
Relative Humidity	95% @ 60°C (non-condensing)

Order Information

DT-B150DL-H	CPU: B150+LGA1151, RAM:Up to 32GB 2 x DP, 1 x HDMI 3 x SATA, 1 x mSATA 4 x USB3.0, 2 x USB2.0, 1 x RS232, 2 x RJ45
-------------	---

Dimensions and Drawing

