

- Kabylake
- Dual Channel
- 4K
- HDMI
- DP
- SIM Slot



RoHS  

Features

- Intel® 7th Generation Core Processors
- 2 x SO-DIMM DDR4/DDR3L Memory, Up to 32GB
- 1 x DP, 1 x HDMI, Supporting 4K Display
- 1 x 2.5" SATA, 1 x mSATA, 1 x M.2 (2242/2280)
- 3 x USB3.0, 3 x USB2.0, 1 x RS232
- 1 x RJ45, 1 x Mini-PCIe for WiFi/BT/3G/4G, 1 x SIM Slot

Specifications

CPU	Intel® Pentium 4415U/Core i3-7100U/Core i5-7200U
Frequency	2.30 GHz/2.40 GHz/2.50 GHz (Up to 3.10 GHz)
BIOS	AMI Source Code
Chipset	SOC
System Memory	DDR4/DDR3L, 2 x SO-DIMM, Up to 32GB
GPU	Intel® HD Graphics 620
Graphic Engine	Direct3D 2015, OpenGL 4.5, OpenCL 2.1
Display Interface	1 x HDMI (Max. 3840 x 2160 @30Hz) 1 x DP (Max. 4096 x 2304 @60Hz)
Network Controller	Realtek 8111H Gigabit Ethernet
Ethernet	1 x RJ45
USB	3 x USB3.0, 3 x USB2.0
Serial Port	1 x RS232
Audio	1 x MIC-IN, 1 x AUDIO-OUT
Mini-PCIe	1 x Full-size Mini-PCIe for mSATA 1 x Full-size Mini-PCIe for WiFi/BT/3G/4G
M.2	1 x M.2 (2242/2280) for SSD
SIM	1 x SIM Slot
Storage	1 x 2.5" SATA 1 x M.2 (2242/2280) for SSD 1 x Full-size mSATA
JAHC	WatchDog Timer Auto Power On RTC Remote Control
Operation System	Windows 10 (64-bit) /Linux
Power Requirement	DC-IN/19V/3.42A
Dimensions (W x D x H)	189.6mm x 148.3mm x 26mm (7.46" x 5.84" x 1.02")
Fanless	No
Construction	Metal
Mounting (Optional)	Desk/Wall Mounting and VESA Mounting Kit (JZ 183)
Color	Black
Operating Temperature	0°C ~ 40°C (32 °F ~ 104 °F) at 0.7m/s Air Flow
Relative Humidity	95% @ 40°C (non-condensing)
Certification	CE, FCC Class B, CCC

Order Information

D67-N2-4415U30H0G-GIA	CPU: Intel® Pentium 4415U	RAM: DDR3L
D67-N1-7100U40H0G-GIA	CPU: Intel® Core i3-7100U	RAM: DDR4
D67-N2-7100U30H0G-GIA	CPU: Intel® Core i3-7100U	RAM: DDR3L
D67-N1-7200U40H0G-GIA	CPU: Intel® Core i5-7200U	RAM: DDR4
D67-N2-7200U30H0G-GIA	CPU: Intel® Core i5-7200U	RAM: DDR3L
Packing List	1 x WiFi Antenna, 1 x Drive Disk, 1 x User Manual 1 x AC Power Cable, 1 x AC Power Adapter	
Optional Item	VESA Mounting Kit (JZ 183)	

Dimensions and Drawing

