

Apollo Lake

Fanless

HDMI

M.2

USB3.0



Features

- Intel® Apollo Lake Processors
- DDR3L-1600MHz, Onboard 2GB
- 1 x HDMI or 1 x VGA
- 1 x mSATA
- 2 x USB3.0, 1 x USB2.0, 2 x RS232
- 1 x RJ45, 1 x M.2 (2230) for WIFI

Specifications

CPU	Intel® Celeron N3350/Atom x5-E3930
Frequency	1.10 GHz(Up to 2.40 GHz)/1.30 GHz (Up to 1.80 GHz)
BIOS	AMI Source Code
Chipset	SOC
System Memory	DDR3L-1600MHz Onboard 2GB
GPU	Intel® HD Graphics 500
Graphic Engine	DirectX 11.1, OpenGL 3.0, OCL 1.1, OpenGL ES 2.0
Network Controller	1 x I210-IT Gigabit Ethernet
Display Interface	1 x HDMI (Max. 3840 x 2160 @30Hz) or 1 x VGA (Max. 1920 x 1080 @60Hz)
Ethernet	1 x RJ45
Internal I/O	1 x USB 2.0, 2 x USB 3.0 2 x RS232 1 x Full-size Mini-PCIe for mSATA 1 x M.2 (2230) for WIFI
Storage	1 x mSATA
JAHC	WatchDog Timer Auto Power On RTC
Operation System	Windows 10 (64-bit)/ Linux
Power Requirement	DC-IN/12V
Dimensions (W x D)	132 x 80 x 52mm (5.15" x 3.12" x 2.03")
Fanless	Yes
Operating Temperature	-20°C ~ 60°C (-4 ~ 140°F) at 0.7m/s Air Flow 0°C ~ 60°C (32 ~ 140°F) at 0.7m/s Air Flow
Relative Humidity	95%@40°C (non-condensing)
Certification	CE, FCC Class B, CCC

Order Information

ISC-261	CPU: Intel® Celeron N3350 CPU: Intel® Atom x5-E3930
Packing List	2 x WiFi Antenna, 1 x Drive Disk, 1 x User Manual, 1 x AC Power Cable, 1 x AC Power Adapter

Dimensions and Drawing

